



- 2.0 resolution
- IP44 rating
- 3-Axis mounting
- ONVIF protocol support
- iOS & Android Free Software
- Free Surveillance software included

IP Camera		
Model	IPD-VF2MP POE	
Version	1.1	
Image Sensor		
Sensor	1/2.8" Sony	
Pixel Size, µm	2.8x2.8	
Resolution, points@fps	Main stream	1920x1080@30, 1280x720@30, 704x576@30
	Sub stream	704x576@30, 320x288@30
Day/Night mode	Auto/Color/Black&White	
Sensitivity, Lux/Iris	Color 0.01Lux@F1.2, Black/White: 0.001 Lux@F1.2	
Dynamic range WDR, dB	72	
S/N ratio, dB	48	
Video functions	AEC, AGS, AWB, ABF, ABLC, OSD, PrivacyMasks	
Codec profile	H.264	Baseline / Main / High
	Exposure mode, s	
	Auto	1/50-1/10000
	Manual	0.256-65.536
Bitrate Type, kb/s	Constant	1024-8192
	Variable	Worst/Worse/General/Good/Better/Best
Lens		
Focal length, mm	2.8-12	
Iris, F	1.4	
Angle of View, °	Horizontal	86 - 25
	Vertical	55 - 14
lens Type	Aspherical	-
	Spherical	+
Lens mount	M12	
Control	Manual	
IR LED		
Distance, m	-	
Number of LEDs, pcs.	-	
Beam Spread, °	-	
Wavelength, nm	-	
IR Cut Filter	-	
Network		
Network Interface	RJ-45 (10/100Base-T)	
Network functions	Cloud/NiP/DDNS/IPFilter/E-mail/NTP/PPPoE/UPNP/FTP/RTSP	
Browser supported	Internet Explorer, Opera, Mozilla Firefox, Google Chrome	
Languages supported	English, Russian, Arabic, French, Poland, Romanian, Hungarian, Italian	
Default IP address	<b>192.168.1.10</b>	
Username	<b>Admin</b>	
Password	<b>Empty by default</b>	
HTTP port	80	
ONVIF port	8899	
RTSP port	554	
RTSP string	rtsp://192.168.1.10:554 /user=admin&password=&channel=1&stream=0.sdp?	
Control port	34567	
Software supported	Free	CMS Partizan
	Mobile software	
iOS	Partizan CCTV, Partizan Cloud, Partizan Pro	
Android	Partizan CCTV, Partizan Cloud, Partizan Pro	
System Integration	Partizan SDK, ONVIF 2.4+	
Dimensions		
Size, mm	Total length	98,5
	Housing	Ø128x98,5
	Bracket	-
Weight, g	270	
Common		
Power Supply	DC12V, A	0.3
	PoE, Class/W	0/6
Alarm	Inputs	-
	Outputs	-
Audio	+	
Memory card	-	
Housing material	Plastic	
Bracket material	-	
IP rating	44	
IK rating	-	
Operating temperature, °C	+10 - +50	
Warranty, years	3	